


1)标准电缆长度2m,  
可供非标准电缆长度




安装方式 [ f / n f ]	齐平	齐平	齐平	
感应距离 S <sub>n</sub> [ mm ]	1.0mm	1.2mm	1.5mm	
型号	NPN N. O	LS-1.0D04N-2	LS-1.2D04N-2	LS-1.5D04N-2
	NPN N. C	LS-1.0D04N2-2	LS-1.2D04N2-2	LS-1.5D04N2-2
	PNP N. O	LS-1.0D04P-2	LS-1.2D04P-2	LS-1.5D04P-2
	PNP N. C	LS-1.0D04P2-2	LS-1.2D04P2-2	LS-1.5D04P2-2
待检测物体标准	铁 4×4×1mm	铁 4×4×1mm	铁 4×4×1mm	
修正系数	Fe37=1/不锈钢约0.85/黄铜约0.5/铝约0.45/铜约0.4			
设定距离 [ mm ]	0-0.8mm	0-0.96mm	0-1.2mm	
工作电压 [ V ]	10-30VDC			
最大负载电流 [ mA ]	200mA			
空载电流 [ mA ]	≤10mA			
电压降 [ V ]	<1.5VDC	<1.5VDC	<1.5VDC	
开关频率 [ Hz ]	2000Hz	2000Hz	2000Hz	
响应时间 [ ms ]	0.1ms/0.1ms	0.1ms/0.1ms	0.1ms/0.1ms	
磁滞 [ S <sub>r</sub> 的百分比]	<15%			
重复精度 [ S <sub>r</sub> 的百分比]	<1%			
环境温度 [ °C ]	-25 - +70°C			
温度漂移 [ S <sub>r</sub> 的百分比]	<10%			
极性保护/短路保护	内置/脉冲			
过载保护电流 [ mA ]	220mA			
壳体材质	不锈钢			
感应面材质	POM			
开关状态显示	LED			
接线方式	2m线缆 (防油、耐折弯)			
防护等级	IP67			
抗冲击	30gn, 11ms			
抗震动	55Hz, 1mm ampl., 3×30min.			
EMC	IEC 60947-5-2			
配件	/			

## 尺寸图和接线图


单位: mm




NPN N. O



PNP N. O



NPN N. C



PNP N. C

